

## GG 320-25 AkLPR

|                                        |                       |
|----------------------------------------|-----------------------|
| <b>Max. Working height</b>             | 32,10 m               |
| <b>Movable up to working height</b>    | 32,10 m               |
| <b>Max. Pitch angle</b>                | 40 %                  |
| <b>Four-wheel drive</b>                | ja                    |
| <b>Drive type</b>                      | Diesel                |
| <b>Non-Marking</b>                     | no                    |
| <b>Construction width</b>              | 2,52 m                |
| <b>Overall dimensions LxWxH</b>        | 11.65 x 2.52 x 2.80 m |
| <b>Ground clearance</b>                | 0,26 m                |
| <b>Transport position height</b>       | 2,80 m                |
| <b>Transport position length</b>       | 11,65 m               |
| <b>Surplus</b>                         | 4,30 m                |
| <b>Dead weight</b>                     | 20100 kg              |
| <b>Track widening</b>                  | 3,31 m                |
| <b>Platform dimensions WxD</b>         | 2.41 x 1.12 m         |
| <b>Max. Basket load / Lifting load</b> | 250 kg                |
| <b>Swing axle</b>                      | ja                    |
| <b>Soot particle filter</b>            | ja                    |
| <b>Basket arm</b>                      | ja                    |
| <b>Swivel range</b>                    | 360°/endless          |
| <b>Rotating work basket</b>            | ja                    |
| <b>Max. lateral reach</b>              | 21,75 m               |



