

## GG 430-25 AKLG

|                                        |                                                            |
|----------------------------------------|------------------------------------------------------------|
| <b>Max. Working height</b>             | 43,00 m                                                    |
| <b>Movable up to working height</b>    | 43,00 m                                                    |
| <b>Max. Pitch angle</b>                | 45 %                                                       |
| <b>Four-wheel drive</b>                | ja                                                         |
| <b>Drive type</b>                      | Diesel                                                     |
| <b>Non-Marking</b>                     | no                                                         |
| <b>Construction width</b>              | 2,46 m                                                     |
| <b>Overall dimensions LxWxH</b>        | 12.80 x 2.46 x 3.07 m                                      |
| <b>Ground clearance</b>                | 0,42 m                                                     |
| <b>Transport position height</b>       | 3,07 m                                                     |
| <b>Transport position length</b>       | 12,80 m                                                    |
| <b>Surplus</b>                         | 5,32 m                                                     |
| <b>Dead weight</b>                     | 20262 kg                                                   |
| <b>Track widening</b>                  | 3,9 m                                                      |
| <b>Platform dimensions WxD</b>         | 1.82 x 0.76 m                                              |
| <b>Max. Basket load / Lifting load</b> | 272 kg                                                     |
| <b>Swing axle</b>                      | no                                                         |
| <b>Basket arm</b>                      | ja                                                         |
| <b>Swivel range</b>                    | endless                                                    |
| <b>Rotating work basket</b>            | ja                                                         |
| <b>Max. lateral reach</b>              | 21,60 m                                                    |
| <b>Special features</b>                | Extremely favorable working diagram, telescoping cage arm, |



