

# GTT 160-25 AkPRG

|                                        |                                                                        |
|----------------------------------------|------------------------------------------------------------------------|
| <b>Max. Working height</b>             | 15,60 m                                                                |
| <b>Movable up to working height</b>    | 15,60 m                                                                |
| <b>Max. Pitch angle</b>                | 45%                                                                    |
| <b>Four-wheel drive</b>                | ja                                                                     |
| <b>Drive type</b>                      | Diesel/4x4                                                             |
| <b>Non-Marking</b>                     | no                                                                     |
| <b>Transport position length</b>       | 9,17 m                                                                 |
| <b>Construction width</b>              | 2,52 m                                                                 |
| <b>Transport position height</b>       | 2,57 m                                                                 |
| <b>Surplus</b>                         | 0,86 m                                                                 |
| <b>Ground clearance</b>                | 0,27 m                                                                 |
| <b>Dead weight</b>                     | 7077 kg                                                                |
| <b>Track widening</b>                  | no                                                                     |
| <b>Platform dimensions WxD</b>         | 2.44 x 0.92 m                                                          |
| <b>Max. Basket load / Lifting load</b> | 454 kg                                                                 |
| <b>Soot particle filter</b>            | ja                                                                     |
| <b>Basket arm</b>                      | ja                                                                     |
| <b>Swivel range</b>                    | 360°                                                                   |
| <b>Rotating work basket</b>            | ja                                                                     |
| <b>Max. lateral reach</b>              | 12,03 m                                                                |
| <b>Special features</b>                | Optionally available with 4 m basket (change of basket load to 272 kg) |



